

COLOURED NO NOISE ACRYLIC ADHESIVE TAPE

PRODUCT DESCRIPTION

Coloured no noise adhesive tape with solvent-free water-based acrylic adhesive. Suitable for medium weight box sealing with manual dispensers or automatic carton sealing machines. Customised colours possible.



FEATURES



No noise unwinding



Solvent free



Printed

MAIN APPLICATIONS



Medium weight box sealing



Manual dispensers



Automatic carton sealing machines

BACKING MATERIAL

BIAXIALLY ORIENTED
POLYPROPYLENE

TYPE OF ADHESIVE

WATER BASED ACRYLIC

AVAILABLE VERSIONS

J = jumbo ET = easy tear

Data referring to tensile strength and elongation at break cannot be applied to ET version.

COLOURS



BLACK



PMS 032 C



PMS 355 C



PMS YELLOW C



PMS 021 C



PMS REFLEX C



PMS 2995 C



OTHER COLORS
ON REQUEST

TECHNICAL DATA	Metric	Value	Test Method
Backing thickness	µm	28	AFERA 5006
Total thickness	µm	48	AFERA 5006
Adhesion to steel	N/cm	2.4	AFERA 5001
Tensile strength	N/cm	45	AFERA 5004
Elongation at break	%	160	AFERA 5004

Technical Informations, storage and product use

The product must be used within 12 months from the delivery date (6 months if jumbo). It is advisable to keep the material in its original packaging, away from heat sources and away from direct light. The storage temperature must be between 15° and 30° C and the relative humidity between 40 and 60%. For storage temperatures other than those indicated, recondition the product to the levels described above. The technical data shown in the data sheets are the average of the analyzes obtained on normal production. Aging can determine the variation of some technical and aesthetic characteristics of the product within the time limits indicated above without affecting its quality and functionality. The technical data shown are reported with a tolerance of +/- 10% and may be modified at any time for production needs or technical updates.

Fabo spa declines all responsibility for direct damage and for the consequences deriving from improper use of the product. It is advisable to check the conformity of the product in relation to the specific conditions of use.

Rev.01_01/03/2023